



GRENADA

Material	steel pipes \varnothing 20 mm / steel profiles D30 x 35 mm
Connection thread	4 x G1/2"
Testing overpressure	1,3 MPa
Max. operating overpressure	1,0 MPa
Max. operating temperature	110 °C
Number of pipes	15, 19, 24, 32, 38



GRENADA 1135 x 600

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input		Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C	paint [W]	chrome [W]	
695/450	30	5,2	2,5	1,270	298	242	156	300	200	415
695/500	30	5,6	2,7	1,270	327	266	171	300	200	465
695/600	30	6,5	3,0	1,270	384	312	201	400	300	565
695/750	30	7,9	3,6	1,226	462	379	247	500	300	715
935/450	30	7,0	3,3	1,269	391	318	204	400	300	415
935/500	30	7,5	3,6	1,269	429	349	224	400	400	465
935/600	30	8,7	4,1	1,269	504	410	264	500	400	565
935/750	30	10,5	4,8	1,269	612	498	320	600	500	715
1135/450	30	8,4	4,0	1,269	467	380	244	500	300	415
1135/500	30	9,0	4,3	1,269	512	417	268	500	400	465
1135/600	30	10,4	4,9	1,269	602	490	315	600	400	565
1135/750	30	12,6	5,7	1,226	742	608	396	700	500	715
1535/450	30	11,2	5,4	1,268	632	514	331	600	400	415
1535/500	30	12,1	5,8	1,268	693	564	363	700	500	465
1535/600	30	13,9	6,5	1,268	815	663	427	800	600	565
1535/750	30	16,9	7,7	1,226	991	812	530	1000	700	715
1775/450	30	13,1	6,3	1,267	739	601	387	700	500	415
1775/500	30	14,2	6,8	1,267	810	659	424	800	600	465
1775/600	30	16,4	7,7	1,267	952	775	498	1000	700	565
1775/750	30	19,9	9,1	1,226	1170	959	625	1200	800	715

Thermal power measuring follows in accordance with EN 442. Chrome surface treatment reduces heating capacity by ~30 %. Accessories (page 64, 65 and 66) is not part of the radiator.

POSSIBILITY OF THE MIDDLE CONNECTION (per order)

direct middle connection standard

direct middle connection with cover

Connection options

	A [mm]	X [mm]
Plastic brackets (RAL 9006, 9016)	88-98	73-83
Metal brackets (Other colours)	84-94	69-79