



COOL ICE



PASTEL YELLOW



RGB LED REMOTE CONTROLLER

VARIANT GLASS - LED, PURE WHITE

VARIANT GLASS - LED

Material	design hardened safety glass steel pipes \varnothing 28 mm / steel profiles 70 x 11 mm
LED lighting bars	white or RGB-with remote controll power supply 230V
Connection thread	2 x G 1/2"
Testing overpressure	0,65 Mpa
Max. operating overpressure	0,5 Mpa
Max. operating temperature	75 °C



VARIANT GLASS - LED, PASTEL YELLOW, rounded polished glass, angular corners

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C	
1810/620	88	45,0	7,2	1,31	989	800	506	mc 50


VARIANT GLASS - LED, PURE WHITE, rounded polished glass, rounded corners

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C	
1810/620	88	45,0	7,2	1,31	989	800	506	mc 50

VARIANT GLASS - LED, COOL ICE, rounded matt glass, rounded corners

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C	
1810/620	88	45,0	7,2	1,31	989	800	506	mc 50

Thermal power measuring follows in accordance with EN442.
Connection fittings and stainless steel rail are not part of the radiator.



Connection options

